

TECHNICAL DATASHEET

BC212



PRODUCT DESCRIPTION

BC212 is a crystalline, high molecular weight thermoplastic polymer made by continuous melt-phase polymerization process followed by solid-state polymerization. BC212 is specially formulated bottle grade PET, characterized by high I.V. and low acetaldehyde. The high I.V. confers good mechanical properties; high burst strengths and reduced bottle distension after filling.

TRPICAL APPLICATION

BC212 is especially suitable for the production of bottles for carbonated drinks. The high I.V. gives the bottle the extra mechanical strength required in hot countries due to the high pressure from carbonation. It can also be used for bottles for non-carbonated and other packaging applications, e.g. edible oil & thermoformed packaging.

TYPICAL DATA

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
PHYSICAL PROPERTIES			
Intrinsic Viscosity ⁽¹⁾	0.84 ± 0.02	dl/g	
DEG Content	< 1.5	% w/w	
Crystalline Density	< 1390	kg/m ³	
Moisture Content ⁽²⁾	< 0.35	% w/w	
POLYMER PROPERTIES			
Acetaldehyde	< 1	ppm	
Color (L)	89 ± 4.0	L-value	IRC 0051
Color (b)	-1.5 ± 2.0	b-value	IRC 0051
Dust Content	< 0.01	% w/w	
Bulk Density	850 ± 10	kg/m ³	ASTM D1895